



## POLYCAB WIRES PVT. LTD.

LIST PRICE NO 01 /2013-14 effective 09<sup>th</sup> April 2013

**POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - FLAME RETARDANT (FR) / FRLS / FRZH CONFORMING TO IS-694:1990 WITH FLEXIBLE BRIGHT ANNEALED ELECTROLYTIC COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 VOLTS**

Size (sq.mm.)	Rate per 90m Coil			Standard Packing 90m Coils	Standard Packing 180m Coils (No. of coils)
	FR	FRLSH	FRZH		
0.75	830	880	950	28	12
1	1070	1100	1200	24	12
1.5	1600	1700	1850	16	10
2.5	2600	2700	3000	12	6
4	3800	4000	4400	8	4
6	5650	6000	6500	6	3
10	9900	10500	11400	1	1
16	15900	17000	18300	1	1

### Notes

- Excise Duty, VAT, Entry Tax, Octroi and any other tax/levy will be charged extra, as per actuals. This is applicable on all Polycab Light Duty Cable products given in this List Price.
- List Price of 180m Coils will be double that of corresponding 90m Coil.
- For Daman despatches minimum order value Rs. 1,00,000 for FOR delivery. For order value below Rs. 1,00,000 freight to customer account
- This Price List is subject to change without notice.
- As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.

POLYCAB INDUSTRIAL JELLY FLOODED COAXIAL CABLES				POLYCAB LAN (COMPUTER) CABLES	
Polycab Gas Injected Physical Polyethylene Foam Insulation with Laminated Aluminium Tape and Aluminium Wire Braid, Jelly Flooded PVC Black Jacketed Industrial Coaxial Cables.				Polycab 4 Pair <u>Unshielded</u> Twisted Pair (UTP) LAN (Computer) Cables	
Size	100m Unarmoured	305m Unarmoured	1000m Armoured	CAT -5 E	Cat 6
RG - 59	1650	5700	---	<u>Unarmoured -Rate per 305 m</u>	
RG - 6	2250	7100	66500	6900	9700
RG - 11	4700	14800	110000	<u>Armoured- rate per 100m</u>	
RG-6 CCS	1500	4700	---	6450	7300
RG-11 CCS	2800	8900	---	Polycab 4 Pair <u>Shielded</u> Twisted Pair (STP) LAN (Computer) Cables	
				<u>STP- rate per 305m</u>	
<b>Note: Please add 7.5% extra for 80% braiding.</b>				10550	13300



## POLYCARB WIRES PVT. LTD.

LIST PRICE NO 01 /2013-14 effective 09<sup>th</sup> April 2013

### POLYCARB INDUSTRIAL TELEPHONE CABLES

### POLYCARB IND 3C FLAT SUBMERSIBLE CABLES

#### TELEPHONE ( SWITCHBOARD ) CABLES

Polycab High Conductivity Solid Annealed Bare Copper industrial Telephone (Switchboard) Cables with High Density Polyethylene Insulation, Paired, Polyester and Sheathed with High Oxygen Index, Fire Retardant, PVC Compound, Grey Outer Sheath generally conforming ITD Specification

#### Rate per 100m coil

No. of Pairs & Size	0.4 mm	0.5 mm	Master Packing
1 Pair	560	750	20
2 Pair	1050	1300	20
3 Pair	1500	2000	16
4 Pair	2000	2600	12
5 Pair	2600	3300	8
10 Pair	--	6400	1
20 Pair	--	12000	1
50 Pair	--	33000	1
100 Pair	--	65000	1

#### ARMOURED TELEPHONE CABLES

No. of Pairs & Size	Rate / 100m	Master Packing 0.5 mm
2 Pair x 0.5 mm	4150	Drums/Coils as required
5 Pair x 0.5 mm	6900	Drums/Coils as required
10 Pair x 0.5 mm	10700	Drums/Coils as required
15 Pair x 0.5 mm	14300	Drums/Coils as required
20 Pair x 0.5 mm	18000	Drums/Coils as required
50 Pair x 0.5 mm	43700	Drums/Coils as required
100 Pair x 0.5 mm	78600	Drums/Coils as required

Polycab PVC Insulated and PVC Sheathed Industrial 3 Core Flat Submersible Cable with Bare Bunched Copper Conductor for Submersible Pump Motors with Voltage Grade upto 1100 Volts as per IS:694/1990

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Cables (No./dia mm)	Rate per 100m (Rs)
1.5	22/.3	6500
2.5	36/.3	10000
4	56/.3	14700

Polycab Special PVC Insulated & PVC Sheathed Industrial 3 Core Flat Submersible Cables with Bare Bunched Copper Conductor for Submersible Pump Motors with Voltage Grade Upto 1100 Volts generally conforming to IS 694/1990.

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Cables (No./dia mm)	Rate per 100m (Rs)
6	84/0.3	22000
10	80/0.4	38400
16	126/0.4	59400
25	196/0.4	92500
35	276/.4	127100
50	396/.4	183500
70	354/.5	265000

#### Notes :

1) The above cables are supplied in 500/1000m drums.

2) Polycab Three Core Flat Submersible Cables Insulated & Sheathed with XLPE can be supplied at the same rates as given above.



# POLYCAB WIRES PVT. LTD.

LIST PRICE NO 01 /2013-14 effective 09<sup>th</sup> April 2013

## PRICE LIST - POLYCAB INDUSTRIAL FLEXIBLE CABLES

**Polycab PVC Insulated Single Core Unsheathed Industrial Flexible Cable conforming to IS 694:1990 with Flexible Bright Annealed Copper Conductor for Voltage Grade upto 1100 Volts**

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	(Rate/100m)	
			Single Core	Packing
0.5	16/.2	5	654	25
0.75	24/.2	8	910	25
1	32/.2	13	1180	20
1.5	30/.25	17	1685	16
2.5	50/.25	24	2750	12
4	56/.3	30	4270	8
6	84/.3	38	6320	6
10	80/.4	52	11100	1
16	126/.4	70	17400	1
25	196/.4	88	27600	1
35	276/.4	110	38500	1
50	396/.4	145	55400	1
70	354/.5	215	78450	1
95	484/.5	260	104000	1
120	608/.5	305	134000	1
150	750/.5	355	167000	1
185	925/.5	415	203000	1
240	1210/.5	500	268000	1
300	1527/.5	585	340000	1
400	2036/.5	695	456000	1
500	2540/.5	790	560000	1

**Polycab PVC Insulated and PVC Round Sheathed Multi Core Bright Annealed Bare Copper Conductor Heavy Duty Industrial Cables for Voltage Grade upto 1100 Volts as per IS: 694:1990**

(Rate/100m)					
Two Core	Three Core	Four Core	1 - 4 Core Packing	5 Core	6 Core
1917	2573	3293	4	4559	5391
2461	3365	4329	4	5949	7158
3140	4327	5616	4	7901	9231
4120	5800	7675	4	10638	12711
6679	9263	12327	3	17303	20714
9950	14300	18800	1	25000	30000
14790	21159	28215	--	--	--
25321	36268	47807	--	--	--
38500	58000	76500	--	--	--
--	99650	131000	--	--	--
--	137500	182000	--	--	--
--	197500	264000	--	--	--
--	--	--	Loading factor for Different Insulation		
--	--	--	FR Insulation :		
--	--	--	FRLSH /HR Insulation :		
--	--	--	HFFR :		
--	--	--	--	--	--

Note: Prices of higher sizes of multi core cables will be given on request.

**Polycab PVC Insulated, PVC Round Sheathed Multi Core Industrial Flexible Cable conforming to IS 694:1990 with Flexible Bright Annealed Copper Conductor for Voltage Grade upto 1100 Volts**

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	(Rate per 100m - Rs)						
			7 Core	10Core	12 Core	14 Core	16 Core	19 Core	24 Core
0.5	16/.2	5	6200	8800	10400	12100	13700	16100	20400
0.75	24/.2	8	8200	11700	13800	16000	18500	21500	27200
1	32/.2	13	10600	15150	17900	20700	23600	28100	35200
1.5	30/.25	17	14700	21000	24900	29100	33000	39100	49600
2.5	50/.25	24	23800	34400	41200	47400	54800	63900	80700
4	56/.3	30	38500						

Polycab Multi Strand Bare Copper conductor XLPE insulated PVC Sheathed Cables				Rate/ 100m
Nominal Area	No/Dia of Strands	Current rating in Air at 40°C	Cu Conductor Unarmoured Cables	Cu Conductor Aluminium Armouring Cables
mm <sup>2</sup>	No/mm		Rs	Rs
4	56/0.3	44	5700	9400
6	84/0.3	55	7600	12400
10	80/0.4	75	13400	19500
16	126/0.4	103	20600	23700
25	196/0.4	126	31100	35000
35	276/0.4	152	43200	49400
50	396/0.4	189	60600	69400
70	354/0.5	240	86300	98700
95	484/0.5	297	115900	133700
120	608/0.5	346	148800	169500
150	750/0.5	390	184900	215800
185	925/0.5	460	226100	256800
240	1210/0.5	552	297900	339000
300	1527/0.5	640	369800	421300
400	2036/0.5	753	493100	554700
500	2530/0.5	865	626500	698500
630	3180/0.5	1001	780700	883400

CCTV CABLES	Rate /100m
CCTV Cables 4+1	CCTV Cables 3+1
4350	3650

**POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - FLAME RETARDANT (FR) / FRLS CONFORMING TO IS-694:1990 WITH FLEXIBLE BRIGHT ANNEALED ELECTROLYTIC COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 VOLTS POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - FLAME RETARDANT (FR) / FRLS CONFORMING TO IS-694:1990 WITH FLEXIBLE BRIGHT ANNEALED ELECTROLYTIC COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 VOLTS**

Project Packing				
Size (sq.mm.)	FR	FRLSH	Packing per Coil	
0.75	2800	2900	300	
1	3600	3700	300	
1.5	3550	5700	300	
2.5	8700	9000	300	
4	8450	8900	200	
6	12550	13350	200	
10	22000	23350	200	
16	35400	37800	200	



# POLYCAB WIRES PVT. LTD.

LIST PRICE NO 01 /2013-14 effective 09<sup>th</sup> April 2013

## POLYCAB SOLAR WIRES / CABLES

Flexible Tinned Copper Conductor Single Core Multistrand, Cross Linked, Zero Halogen Low Smoke Insulation and Cross Linked Low Smoke Sheathing , Heat Resistant upto 120°C and UV Resistant Solar Cables

Flexible Bare Copper Conductor Multistrand XLPE / PVC Insulated and UV Stabilized PVC Sheathed Single Core and Multicore Solar Cables

Size in sq mm	Rate Per 100m
1.5	4500
2.5	6200
4	8800
6	12000
10	18800
16	27900
25	43200
35	58800
50	84300
70	116700
95	149100

Size in sq mm	Rate Per 100m
1.5	2600
2.5	4200
4	6400
6	9250
10	15800
16	23800
25	36800
35	51100
50	73500
70	101900
95	138600
120	172200
150	213900
185	273000
2 C x 16	52200
2 C x 25	80500

## POLYCAB BUILDING MANAGEMENT SYSTEM CABLE (BMS)

Flexible Bare Copper Conductor, PVC Insulated, Cross Laid Up, Overall Aluminium Mylar Tape Shielded along with ATC Drain Wire PVC Outer Sheath BMS Cables (Rate/100m)

Cores	0.5 sq.mm (16/.2)	0.75 sq.mm (24/.2)	1.0 sq.mm (32/.2)	1.5 sq.mm (30/.25)	2.5 sq.mm (50/.25)			
2	3700	4300	5200	6300	10500			
3	4400	5600	6600	8400	12700			
4	5400	6700	8200	10700	16400			
5	6200	7770	10000	12600	19800			
6	7000	9300	11400	14700	24600			
7	7770	10400	12900	16900	26800			
10	10800	14100	17900	23700	38000			
12	12600	16700	20900	27900	45200			
14	14400	19000	24100	32350	51800			
16	16300	21900	27100	36300	59700			
19	18700	25100	32000	43000	69200			
24	23300	31400	39800	54200	87100			

Note : 3% Extra Charges for Drum Packing



# POLYCAB WIRES PVT. LTD.

LIST PRICE NO 01 /2013-14 effective 09<sup>th</sup> April 2013

POLYCAB INDUSTRIAL WELDING CABLES				Polycab Industrial Speaker Wires		
Polycab Flexible Copper Conductor Welding Cable upto 1100 Volts as per IS-9857 (Rate per 100 mtr)				Speaker Wires (Oxygen Free) (Rate per 90 mtr)		
Nominal Area of Conductor (sq mm)	Current Carrying Capacity	Conductor Constn. Strands/ Dia in mm	TPR Insulation Rate/100m (Rs)	Size 23/36	Size 40/36	Size 70/36
16	120	509/0.2	22000	1700	2700	4700
25	160	796/0.2	31500			
35	230	1115/0.2	43000	Size 23/38	Size 40/38	Size 70/38
50	400	703/0.3	61000	1200	2000	3150
70	600	999/0.3	87000	** Flame Retardant, Heat Resistant upto 90°C & Oil Resistant		
95	700	1346/0.3	115000			
120	1100	1699/0.3	147500			

POLYCAB INDUSTRIAL BRAIDED CABLES								
Polycab Annealed Bare Cu Flexible Conductor PVC Insulated, Tinned Cu Braided (Screened) PVC Sheathed Flexible Unarmoured Cables 1100 Volts. (Rate per 100 Mtr)								
Cores	7/36	0.5 sq.mm (16/.2)	0.75 sq.mm (24/.2)	1.0 sq.mm (32/.2)	1.5 sq.mm (30/.25)	4 sq.mm. (56/.3)	6 sq mm (84/.3)	
2	4300	5400	6930	7700	9900			
3	5400	6700	8500	9100	12100	26600	34200	
4	6700	8400	10500	11700	15100	31400	49700	
5	8100	10100	14000	15700	18600			
6	9250	11600	15000	16600	22600			
7	9900	12400	16300	18300	24200			
8	11800	14700	19200	20000	27700			
10	14100	17650	23600	26300	35200			
12	16100	20200	26500	29400	41000			
14	17600	22000	30250	31500	48100			
16	20400	25500	33400	38300	52900			
19	23400	29200	39000	45200	62900			
24	28980	36200	46400	56600	77600			
27	38800	48500	63600	74500	99400			
37	51100	63850	84200	140200	133000			

POLYCAB MULTICORE STEEL BRAIDED CABLES (Rate / 100 M)								
Flex Bare Copper Conductor,PVC Insulated, Cores Laid Up Together PVC Inner Sheathed, GI Wire Braided (Flexible Armouring), Overall PVC Sheathed Steel Braided Cables.								
Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	2 Core	3 Core	4 Core	Core	1.5 sq.mm (30/.25)	2.5 sq.mm (50/.25)	
1.5	30/.25	8700	11550	14900	5	17850	27400	
2.5	50/.25	13000	17500	22300	6	20700	32100	
4	56/.3	18800	25200	33000	7	23600	36800	
6	84/.3	26500	36000	46600	8	26600	40500	
10	80/.4	39000	54100	71700	9	29300	45000	
16	126/.4	59000	82600	108300	10	32000	50000	
25	196/.4	89150	126400	167200	12	37500	58900	
35	276/.4	122000	174000	229300	15	46100	73100	
50	396/.4	171800	246000	325300	16	48800	77500	
70	354/.5	258200	371800	493200	18	54300	86300	
95	484/.5	348400	502600	667800	19	57900	90700	
120	608/.5	433450	627200	833400	21	63200	99700	
150	750/.5	541300	783300	1040100	24	71400	112900	
185	925/.5	663900	965400	1280900				
240	1210/.5	861850	1250200	1661400				
300	1527/.5	1075200	1561250	2076600				

Note : 3% Extra Charges for Drum Packing



# POLYCAB WIRES PVT. LTD.

LIST PRICE NO 01 /2013-14 effective 09<sup>th</sup> April 2013

## POLYCAB ALUMINIUM WIRES & CABLES

POLYCAB <u>SINGLE CORE</u> PVC INSULATED 1100 VOLTS SOLID ALUMINIUM CONDUCTOR WIRES AS PER IS 694		POLYCAB <u>SINGLE CORE</u> PVC INSULATED 1100 VOLTS STRANDED ALUMINIUM CONDUCTOR WIRES AS PER IS 694		POLYCAB PVC INSULATED AND SHEATHED <u>TWIN CORE &amp; THREE CORE</u> FLAT CABLES 1100 VOLTS EACH CORE HAVING SINGLE STRANDED ALUMINIUM CONDUCTOR SERVICE CABLES AS PER IS 694		
SQ.MM	RATE/ 100M	SQ.MM	RATE/ 100M	NO.OF CORES	SQ.MM	RATE/ 100M
1.5	380	1.5	380	2	1.5	1400
2.5	590	2.5	590	2	2.5	2000
4	780	4	870	2	4	2800
6	1155	6	1200	2	6	3700
10	1785	10	1800	2	10	5700
POLYCAB <u>SINGLE CORE</u> PVC INSULATED & SHEATHED 1100 VOLTS STRANDED ALUMINIUM CONDUCTOR WIRES AS PER IS 694		16	2600	2	16	7600
		25	4050	2	25	10700
		35	5450	2	35	13650
		50	7350	2	50	17400
SQ.MM	RATE/ 100M	70	9800	2	50	17400
1.5	590	95	11400	3	1.5	1900
2.5	730	120	16600	3	2.5	2800
4	1400	150	20500	3	4	4000
6	1900	185	25600	3	6	5500
10	2600	240	33300	3	10	8100
16	3700	300	41500	3	16	11000
25	5400	400	53350	3	25	15550
35	6900	500	67900	3	35	20100
50	9150	630	86000	3	50	25600
POLYCAB PVC INSULATED AND SHEATHED <u>TWIN CORE &amp; THREE CORE</u> FLAT CABLES 1100 VOLTS EACH CORE HAVING SINGLE SOLID ALUMINIUM CONDUCTOR SERVICE CABLES AS PER IS 694				POLYCAB <u>XLPE</u> INSULATED AND PVC SHEATHED CABLE WITH EACH CORE HAVING STRANDED ALUMINIUM CONDUCTOR SERVICE CABLES GENERALLY CONFORMING TO IS 694.		
NO.OF CORES	SQ.MM		RATE/ 100M	NO.OF CORES	SQ.MM	RATE/100M
2	1.5		1300	2	1.5	1500
2	2.5		1900	2	2.5	2000
2	4		2600	2	4	2600
2	6		3600	2	6	3700
2	10		5500	2	10	4600
3	1.5		1800	2	16	6700
3	2.5		2700			
3	4		4000			
3	6		5150			
3	10		7900			



# POLYCAB WIRES PVT. LTD.

LIST PRICE NO 01 /2013-14 effective 09<sup>th</sup> April 2013

## POLYCAB INSTRUMENTATION CABLES

**Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Mylar/Drain Wire Inner sheathed Unarmoured PVC Outer Sheathed Instrumentation Cable.**

### INDIVIDUAL & OVERALL SHIELDED - UNARMoured INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	2	0.5	91	0.75	103	1	120	1.5	147	2.5	210
PAIR	3	0.5	125	0.75	142	1	168	1.5	206	2.5	299
PAIR	4	0.5	156	0.75	182	1	213	1.5	267	2.5	389
PAIR	5	0.5	190	0.75	220	1	260	1.5	327	2.5	479
PAIR	6	0.5	223	0.75	260	1	308	1.5	385	2.5	573
PAIR	7	0.5	253	0.75	297	1	353	1.5	446	2.5	663
PAIR	8	0.5	284	0.75	334	1	396	1.5	503	2.5	747
PAIR	10	0.5	349	0.75	411	1	489	1.5	625	2.5	926
PAIR	12	0.5	411	0.75	492	1	585	1.5	745	2.5	1103
PAIR	14	0.5	479	0.75	567	1	678	1.5	860	2.5	1277
PAIR	16	0.5	541	0.75	641	1	767	1.5	977	2.5	1452
PAIR	19	0.5	636	0.75	755	1	900	1.5	1151	2.5	1720
PAIR	24	0.5	794	0.75	941	1	1126	1.5	1447	2.5	2158
TRIAD	2	0.5	112	0.75	131	1	156	1.5	197	2.5	287
TRIAD	3	0.5	155	0.75	183	1	219	1.5	279	2.5	414
TRIAD	4	0.5	195	0.75	234	1	281	1.5	362	2.5	543
TRIAD	5	0.5	239	0.75	286	1	345	1.5	445	2.5	674
TRIAD	6	0.5	280	0.75	338	1	410	1.5	529	2.5	803
TRIAD	7	0.5	319	0.75	387	1	471	1.5	616	2.5	930
TRIAD	8	0.5	360	0.75	436	1	531	1.5	694	2.5	1051
TRIAD	10	0.5	443	0.75	539	1	661	1.5	860	2.5	1305
TRIAD	12	0.5	530	0.75	645	1	784	1.5	1024	2.5	1558
TRIAD	14	0.5	610	0.75	745	1	909	1.5	1187	2.5	1809
TRIAD	16	0.5	691	0.75	844	1	1031	1.5	1348	2.5	2065
TRIAD	19	0.5	813	0.75	996	1	1216	1.5	1593	2.5	2441
TRIAD	24	0.5	1014	0.75	1244	1	1522	1.5	2004	2.5	3068



# POLYCAB WIRES PVT. LTD.

LIST PRICE NO 01 /2013-14 effective 09<sup>th</sup> April 2013

## POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Mylar/Drain Wire Inner sheathed GI Steel Wire Round-Strip Armoured PVC Outer Sheathed Instrumentation Cables

### INDIVIDUAL & OVERALL SHIELDED - ARMOURED INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	2	0.5	131	0.75	138	1	155	1.5	181	2.5	247
PAIR	3	0.5	168	0.75	180	1	205	1.5	253	2.5	335
PAIR	4	0.5	204	0.75	240	1	262	1.5	315	2.5	414
PAIR	5	0.5	252	0.75	273	1	313	1.5	368	2.5	502
PAIR	6	0.5	289	0.75	316	1	349	1.5	429	2.5	590
PAIR	7	0.5	322	0.75	356	1	398	1.5	487	2.5	673
PAIR	8	0.5	355	0.75	380	1	441	1.5	544	2.5	754
PAIR	10	0.5	414	0.75	459	1	534	1.5	664	2.5	924
PAIR	12	0.5	484	0.75	540	1	629	1.5	782	2.5	1092
PAIR	14	0.5	552	0.75	615	1	721	1.5	897	2.5	1258
PAIR	16	0.5	617	0.75	690	1	812	1.5	1013	2.5	1428
PAIR	19	0.5	719	0.75	805	1	945	1.5	1186	2.5	1680
PAIR	24	0.5	885	0.75	993	1	1175	1.5	1481	2.5	2094
TRIAD	2	0.5	153	0.75	160	1	185	1.5	239	2.5	320
TRIAD	3	0.5	201	0.75	230	1	265	1.5	324	2.5	431
TRIAD	4	0.5	256	0.75	284	1	331	1.5	396	2.5	558
TRIAD	5	0.5	305	0.75	339	1	385	1.5	484	2.5	681
TRIAD	6	0.5	349	0.75	379	1	453	1.5	567	2.5	803
TRIAD	7	0.5	395	0.75	431	1	512	1.5	648	2.5	922
TRIAD	8	0.5	419	0.75	481	1	571	1.5	725	2.5	1034
TRIAD	10	0.5	511	0.75	584	1	698	1.5	888	2.5	1275
TRIAD	12	0.5	599	0.75	688	1	821	1.5	1050	2.5	1514
TRIAD	14	0.5	684	0.75	787	1	944	1.5	1210	2.5	1753
TRIAD	16	0.5	769	0.75	887	1	1066	1.5	1369	2.5	1992
TRIAD	19	0.5	898	0.75	1038	1	1249	1.5	1613	2.5	2345
TRIAD	24	0.5	1108	0.75	1290	1	1556	1.5	2012	2.5	2931





# POLYCAB WIRES PVT. LTD.

LIST PRICE NO 01 /2013-14 effective 09<sup>th</sup> April 2013

## POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad/Quad laid up together with Al Inner sheathed Mylar/Mylar/Drain Wire Unrmoured PVC Outer Sheathed Instrumentation Cable.

### OVERALL SHIELDED - UNARMOURED INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	1	0.5	46	0.75	49	1	58	1.5	70	2.5	97
PAIR	2	0.5	71	0.75	81	1	97	1.5	175	2.5	175
PAIR	3	0.5	92	0.75	108	1	132	1.5	170	2.5	248
PAIR	4	0.5	113	0.75	135	1	165	1.5	217	2.5	319
PAIR	5	0.5	133	0.75	161	1	199	1.5	263	2.5	395
PAIR	6	0.5	155	0.75	188	1	233	1.5	311	2.5	470
PAIR	7	0.5	174	0.75	213	1	266	1.5	356	2.5	542
PAIR	8	0.5	194	0.75	238	1	299	1.5	402	2.5	613
PAIR	10	0.5	233	0.75	289	1	364	1.5	497	2.5	754
PAIR	12	0.5	272	0.75	340	1	437	1.5	589	2.5	897
PAIR	14	0.5	312	0.75	398	1	502	1.5	678	2.5	1037
PAIR	16	0.5	357	0.75	447	1	566	1.5	770	2.5	1178
PAIR	19	0.5	417	0.75	525	1	665	1.5	906	2.5	1396
PAIR	24	0.5	493	0.75	650	1	826	1.5	1131	2.5	1749
TRIAD	1	0.5	55	0.75	62	1	73	1.5	93	2.5	132
TRIAD	2	0.5	91	0.75	106	1	131	1.5	168	2.5	245
TRIAD	3	0.5	122	0.75	145	1	180	1.5	238	2.5	353
TRIAD	4	0.5	152	0.75	184	1	229	1.5	305	2.5	460
TRIAD	5	0.5	182	0.75	224	1	280	1.5	374	2.5	572
TRIAD	6	0.5	211	0.75	262	1	330	1.5	444	2.5	681
TRIAD	7	0.5	240	0.75	299	1	377	1.5	511	2.5	787
TRIAD	8	0.5	269	0.75	336	1	425	1.5	584	2.5	892
TRIAD	10	0.5	326	0.75	411	1	526	1.5	719	2.5	1102
TRIAD	12	0.5	386	0.75	491	1	625	1.5	853	2.5	1313
TRIAD	14	0.5	448	0.75	565	1	720	1.5	988	2.5	1523
TRIAD	16	0.5	505	0.75	642	1	818	1.5	1121	2.5	1732
TRIAD	19	0.5	591	0.75	752	1	962	1.5	1323	2.5	2053
TRIAD	24	0.5	735	0.75	938	1	1200	1.5	1663	2.5	2577
QUAD	1	0.5	66	0.75	75	1	91	1.5	116	2.5	168
QUAD	2	0.5	111	0.75	133	1	163	1.5	215	2.5	317
QUAD	3	0.5	152	0.75	184	1	228	1.5	306	2.5	462
QUAD	4	0.5	191	0.75	234	1	295	1.5	396	2.5	608
QUAD	5	0.5	230	0.75	287	1	361	1.5	488	2.5	
QUAD	6	0.5	270	0.75	337	1	426	1.5	583	2.5	



# POLYCAB WIRES PVT. LTD.

LIST PRICE NO 01 /2013-14 effective 09<sup>th</sup> April 2013

## POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Core/Pair/Triad/Quad laid up together with Al Inner sheathed GI Steel Wire Mylar/Mylar/Drain Wire Round-Strip Armoured PVC Outer Sheathed Instrumentation

### OVERALL SHIELDED - ARMOURED INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	1	0.5	64	0.75	70	1	78	1.5	92	2.5	126
PAIR	2	0.5	96	0.75	111	1	125	1.5	156	2.5	241
PAIR	3	0.5	121	0.75	141	1	165	1.5	230	2.5	326
PAIR	4	0.5	144	0.75	172	1	227	1.5	284	2.5	404
PAIR	5	0.5	191	0.75	227	1	269	1.5	353	2.5	493
PAIR	6	0.5	215	0.75	259	1	310	1.5	390	2.5	576
PAIR	7	0.5	235	0.75	286	1	347	1.5	439	2.5	655
PAIR	8	0.5	258	0.75	320	1	378	1.5	490	2.5	735
PAIR	10	0.5	320	0.75	373	1	452	1.5	591	2.5	893
PAIR	12	0.5	347	0.75	434	1	529	1.5	693	2.5	1054
PAIR	14	0.5	392	0.75	492	1	603	1.5	792	2.5	1211
PAIR	16	0.5	436	0.75	550	1	676	1.5	892	2.5	1375
PAIR	19	0.5	503	0.75	637	1	786	1.5	1041	2.5	1532
PAIR	24	0.5	608	0.75	777	1	964	1.5	1296	2.5	2006
TRIAD	1	0.5	74	0.75	84	1	97	1.5	118	2.5	164
TRIAD	2	0.5	118	0.75	143	1	170	1.5	211	2.5	329
TRIAD	3	0.5	151	0.75	188	1	240	1.5	304	2.5	457
TRIAD	4	0.5	191	0.75	250	1	298	1.5	395	2.5	562
TRIAD	5	0.5	241	0.75	307	1	371	1.5	457	2.5	686
TRIAD	6	0.5	286	0.75	356	1	412	1.5	534	2.5	807
TRIAD	7	0.5	318	0.75	380	1	462	1.5	606	2.5	923
TRIAD	8	0.5	351	0.75	421	1	515	1.5	680	2.5	1040
TRIAD	10	0.5	400	0.75	506	1	623	1.5	826	2.5	1273
TRIAD	12	0.5	466	0.75	591	1	732	1.5	974	2.5	1507
TRIAD	14	0.5	527	0.75	673	1	837	1.5	1119	2.5	1745
TRIAD	16	0.5	590	0.75	757	1	943	1.5	1264	2.5	1977
TRIAD	19	0.5	683	0.75	880	1	1101	1.5	1487	2.5	2328
TRIAD	24	0.5	836	0.75	1083	1	1366	1.5	1850	2.5	2905
QUAD	1	0.5	86	0.75	100	1	116	1.5	144	2.5	215
QUAD	2	0.5	146	0.75	174	1	223	1.5	288	2.5	417
QUAD	3	0.5	191	0.75	232	1	297	1.5	396	2.5	562
QUAD	4	0.5	251	0.75	319	1	387	1.5	480	2.5	723
QUAD	5	0.5	308	0.75	380	1	446	1.5	582	2.5	883
QUAD	6	0.5	357	0.75	442	1	519	1.5	681	2.5	



# POLYCAB WIRES PVT. LTD.

LIST PRICE NO 01 /2013-14 effective 09<sup>th</sup> April 2013

## POLYCAB RUBBER CABLES

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED , PC TAPE , PCP  
OUTERSHEATHED ELASTOMERIC RUBBER CABLE (Rate Per Mtr)

Size Sq.mm	1 Core	2 Core	3 Core	4 Core	6 Core	7 Core	8 Core	10 Core	12 Core	16 Core	19 Core
0.5	33	87	95	120							
0.75	39	105	115	150							
1	44	120	137	175							
1.5	56	148	175	225	307	370	440	555	640	830	980
2.5	78	200	250	320	465	555	645	780	930	1190	1430
4	110	270	330	430							
6	175	400	500	670							
10	250	645	815	1065							
16	360	920	1200	1570							
25	530	--	1725	2250							
35	675	--	2300	3020							
50	925	--	2970	3890							
70	1390	--	4425	5835							
95	1825	--	5885	7750							
120	2265	--	7265	9600							
150	2780	--	8900	11780							
185	3410	--	10925	14470							
240	4400	--	14170	17300							
300	5500	--	17760	23530							



## POLYCAB WIRES PVT. LTD.

LIST PRICE NO 01 /2013-14 effective 09<sup>th</sup> April 2013

**POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED, UNARMoured POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION**

SIZE	5 PAIR	10 PAIR	20 PAIR	50 PAIR	100 PAIR	200 PAIR
0.5	50	90	160	360	700	1400

**POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED, G.S.TAPE ARMoured POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION**

SIZE	5 PAIR	10 PAIR	20 PAIR	50 PAIR	100 PAIR	200 PAIR
0.5	95	140	200	450	800	1500