

NKS100R100AC3P

Simpact NKS100R circuit breaker - 3P - 100 A - 10 kA - 415 V - fixed pick-up

Main

Device short name	Simpact NKS100R
Circuit breaker name	Simpact NKS100R
Poles description	3P
Network type	AC
Mounting mode	Fixed
[In] rated current	100 A at 40 °C
[Ue] rated operational voltage	415 V AC 50/60 Hz conforming to IEC 60947-2 415 V AC 50/60 Hz conforming to IS 13947 part 2
Circuit breaker rating code	R
Breaking capacity	I _{cu} = 10 kA at 415 V AC , 50 Hz conforming to IEC 60947-2 I _{cu} = 10 kA at 415 V AC , 50 Hz conforming to IS 13947 part 2
Utilisation category	Category A
Trip unit name	MA
Trip unit technology	Magnetic
Long time pick-up adjustment type I _r	Fixed
Pole distance	30 mm

Complementary

Network frequency	50 Hz
Control type	Toggle
Mounting support	Backplate
Upside connection	Front
Downside connection	Front
[Ui] rated insulation voltage	690 V AC 50 Hz conforming to IEC 60947-2 690 V AC 50 Hz conforming to IS 13947 part 2
[Uimp] rated impulse withstand voltage	8 kV conforming to IEC 60947-2 8 kV conforming to IS 13947 part 2
[Ics] rated service breaking capacity	5 kA (I _{cs} = 50 %) at 415 V AC 50 Hz conforming to IEC 60947-2 5 kA (I _{cs} = 50 %) at 415 V AC 50 Hz conforming to IS 13947 part 2
Mechanical durability	10000 cycles
Electrical durability	1500 cycles (at 415 V AC , 50 Hz) category A , conforming to IEC 60947-2 1500 cycles (at 415 V , conforming to IS 13947 part 2
Connection pitch	30 mm without spreader 36.5 mm with spreader
Protection type	Fully magnetic
Height	153 mm
Width	90 mm
Depth	83 mm
Mechanical robustness	Shocks conforming to IEC 68-2-27 Vibrations conforming to IEC 68-2-6

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Standards	IEC 60947-1 IEC 60947-2 IS 13947 part 1 IS 13947 part 2
IP degree of protection	IP20, with toggle (bare circuit-breaker with terminal shields) conforming to IEC 60529 IP20, with toggle (circuit-breaker installed in a switchboard) conforming to IEC 60529 IP40, with direct rotary handle (bare circuit-breaker with terminal shields) conforming to IEC 60529 IP42, with direct rotary handle (circuit-breaker installed in a switchboard) conforming to IEC 60529
IK degree of protection	IK07, with toggle (bare circuit-breaker with terminal shields) conforming to IEC 62262 IK07, with direct rotary handle (bare circuit-breaker with terminal shields) conforming to IEC 62262 IK07, with toggle (circuit-breaker installed in a switchboard) conforming to IEC 62262 IK07, with direct rotary handle (circuit-breaker installed in a switchboard) conforming to IEC 62262
Pollution degree	3 , conforming to IEC 60947
Ambient air temperature for operation	-5...50 °C
Ambient air temperature for storage	-50...85 °C
Climatic withstand	85 °C (exposure to dry heat) conforming to IEC 68-2-2 95 % relative humidity at 55 °C (continuous exposure to damp heat) conforming to IEC 68-2-30 - 55 °C (exposure to cold) conforming to IEC 68-2-1 Class 2 (salt mist) conforming to IEC 68-1-52
RoHS EUR status	Will not be compliant