



### Main

Commercial Status	Commercialised
Range of product	ZENcelo
Product or component type	Switch
Device application	Bell switch
Local signalling	Indicator light neon amber
Number of gangs	1 gang

### Complementary

Device mounting	Flush Surface
Number of cables	1 2.5 mm <sup>2</sup> stranded 1 2.5 mm <sup>2</sup> solid 3 1.5 mm <sup>2</sup> stranded 3 1.5 mm <sup>2</sup> solid
Rated current	6 A 240 V AC 50/60 Hz
Material	Steel metal parts Polycarbonate dolly Polycarbonate cover Polycarbonate base Copper metal parts Brass metal parts
Load type	Fluorescent lamp Inductive Resistive
Connections - terminals	Brass rod terminals
Width	58 mm
Height	37.9 mm
Depth	23.55 mm

### Environment

Ambient air temperature for operation	<= 35 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant
Operating altitude	2000 m
Standards	IS 3854

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.